



EXTREME QUALITY

THE LARGEST SELECTION
OF WINCHES ON THE MARKET





OWN RESEARCH AND DEVELOPMENT








AVAILABLE IN 46 COUNTRIES





THE DRAGON WINCH TRUCK SERIES COMPRISES EXTRA STRONG
AND SOLID WINCHES INTENDED FOR USE IN THE MOST EXTREME CONDITIONS.

DEDICATED FOR:



DRAGON WINCH series TRUCK





DWT 22000 HD

Dedicated for: special trucks, tow trucks / industrial vehicles

Voltage: 24 V Motor: 9,2 hp

Pulling rate: 22000 lb / 9979 kg

Reduction: 463:1 Gear: 3 stage planetary Brake: dynamic

Length of the wire rope: 31 m **Length of the synthetic rope:** 21 m

Overall size (LxWxH): 637 mm x 217 mm x 271 mm

Weight: 80 kg Screws: 8

Spacing of mounting screws: $254 \text{ mm} \times 114 \text{ mm} / 254 \text{ mm} \times 164 \text{ mm}$

THE SET INCLUDES:

wire rope or synthetic rope
rope hook
control box
roller guides
remote control
and wireless remote control
mounting screws

Rope winding speed and power consumption (the first rope layer on the drum)

rope load	kg		2721	5443	9979	
rope speed	m/min	4,5	3,7	3,0	1,7	
power consumption 24 V	amp	42	112	232	305	

Pulling force depending on rope layer

rope layer		1	2	3	4	5
rope pull	kg	9979	7883	6786	5887	4889
rope lenght on the drum	m	5,1	11,1	18,4	26,5	31,0



DWT 18000 HD

Dedicated for: off-road vehicles, tow trucks / industrial vehicles

Voltage: 24 V Motor: 9,0 hp

Pulling rate: 18000 lb / 8165 kg Gear: 3 stage planetary Reduction: 358:1 Brake: dynamic

Length of the wire rope: 31 m **Length of the synthetic rope:** 21 m

Overall size (LxWxH): 586 mm x 196 mm x 265 mm

Weight: 63 kg Screws: 4

Spacing of mounting screws: 254 mm x 114 mm

THE SET INCLUDES:

wire rope or synthetic rope
rope hook
control box
roller guides
or aluminum fairlead
remote control
and wireless remote control
mounting screws

Rope winding speed and power consumption (the first rope layer on the drum)

rope load	kg		2721	5443	8165
rope speed	m/min	5,5	4,1	3,1	1,5
power consumption 24 V	amp	39	105	214	280

rope layer		1	2	3	4	5
rope pull	kg	8165	6450	5552	4817	4001
rope lenght on the drum	m	5.2	11.4	19.0	27.8	31.0



DRAGON WINCH series TRUCK



DWT 16000 HD

Dedicated for: off-road vehicles, tow trucks / industrial vehicles

Voltage: 12 V or 24 V **Motor:** 7,8 hp

Pulling rate: 16000 lb / 7257 kg

Gear: 3 stage planetary **Reduction:** 358:1 **Brake:** dynamic

Length of the wire rope: 31 m **Length of the synthetic rope:** 21 m

Overall size (LxWxH): 574 mm x 196 mm x 266 mm

Weight: 62 kg Screws: 4

Spacing of mounting screws: 254 mm x 114 mm

THE SET INCLUDES:

• wire rope or synthetic rope
• rope hook
• control box
• roller guides
or aluminum fairlead
• remote control
and wireless remote control
• mounting screws

Rope winding speed and power consumption (the first rope layer on the drum)

rope load	kg		2902	5806	7257	
rope speed	m/min	5,3	3,9	2,7	1,6	
power consumption 12 V	amp	64	114	231	440	
power consumption 24 V	amp	39	108	219	250	

Pulling force depending on rope layer

rope layer		1	2	3	4	5
rope pull	kg	7257	6020	5182	4496	3734
rope lenght on the drum	m	5.3	11.5	19.3	27.9	31.0



DWT 16000 HDL

Dedicated for: special trucks **Voltage:** 12 V lub 24 V

Motor: 7,8 hp

Pulling rate: 16000 lb / 7257 kg

Gear: 3 stage planetary **Reduction:** 358:1 **Brake:** dynamic

Length of the wire rope: 60 m

Overall size (LxWxH): 792 mm x 196 mm x 266 mm

Weight: 75 kg Screws: 4

Spacing of mounting screws: 480 mm x 114 mm

THE SET INCLUDES:

- · wire rope
- · rope hook
- · control box
- · remote control
- and wireless remote control
 mounting screws

Rope winding speed and power consumption (the first rope layer on the drum)

rope load	kg		2902	5806	7257
rope speed	m/min	5,3	3,9	2,7	1,3
power consumption 12 V	amp	64	114	231	440
power consumption 24 V	amp	39	108	219	250

rope layer		1	2	3	4
rope pull	kg	7257	6020	5182	4496
rope lenght on the drum	m	12,7	28,1	46,4	60,0

DRAGON WINCH series TRUCK



DWT 14000 HD

Dedicated for: special trucks, tow trucks / industrial vehicles

Voltage: 12 V lub 24 V

Motor: 7,8 hp

Pulling rate: 14000 lb / 6350 kg

Gear: 3 stage planetary Reduction: 265:1 Brake: dynamic

Length of the wire rope: 20 m

Overall size (LxWxH): 537 mm x 159 mm x 246 mm

Weight: 40 kg Screws: 4

Spacing of mounting screws: 254 mm x 114 mm



Rope winding speed and power consumption (the first rope layer on the drum)

rope load	kg		2721	5443	6350
rope speed	m/min	6	4,5	2,9	1,1
power consumption 12 V	amp	61	206	359	418
power consumption 24 V	amp	38	103	207	240


Pulling force depending on rope layer

rope layer		1	2	3	4	
rope pull	kg	6350	5016	4318	3746	
rope lenght on the drum	m	4,8	10,8	17,5	20,0	

THE SET INCLUDES:

- · wire rope
- · rope hook
- control box
- · roller guides
- · remote control

and wireless remote control mounting screws





DRAGON WINCH MAVERICK

THE DRAGON WINCH MAVERICK SERIES COMPRISES PROVEN AND TOUGH WINCHES INTENDED FOR MANY DIFFERENT KINDS OF USE.

DEDICATED FOR





AVAILABLE ALSO WITH CONTROL BOX ON THE FASTENING BARS



DWM 13000 HD

Dedicated for: off-road vehicles, tow trucks/ industrial vehicles

Voltage: 12 V or 24 V **Motor:** 6,8 hp

Pulling rate: 13000 lb / 5897 kg

Gear: 3 stage planetary **Reduction:** 265:1 **Brake:** dynamic

Length of the wire rope: 30 m. Length of the synthetic rope: 30 m $\,$

Overall size (LxWxH): 537 mm x 159 mm x 246 mm

Weight: 43 kg Screws: 4

Spacing of mounting screws: 254 mm x 114 mm

THE SET INCLUDES:

- wire rope or synthetic rope
 - · rope hook
 - · control box
 - · roller guides
 - or aluminum fairlead
 - · remote control
- and wireless remote control
 - · mounting screws

Rope winding speed and power consumption (the first rope layer on the drum)

rope load	kg		1814	3629	5897
rope speed	m/min	5,9	4,4	2,8	0,8
power consumption 12 V	amp	58	158	314	448
power consumption 24 V	amp	35	89	178	245

Pulling force depending on rope layer

rope layer		1	2	3	4	5
rope pull	kg	5897	4658	4009	3463	2889
rope lenght on the drum	m	4.9	11.0	17.8	26.0	30.0



DWM 12000 HD

Dedicated for: off-road vehicles, tow trucks/ industrial vehicles

Voltage: 12 V Motor: 6,8 hp

Pulling rate: 12000 lb / 5443 kg

Gear: 3 stage planetary Reduction: 265:1 Brake: dynamic

Length of the wire rope: 30 m Length of the synthetic rope: 30 m

Overall size (LxWxH): 537 mm x 159 mm x 243 mm

Weight: 41 kg Screws: 4

Spacing of mounting screws: 254 mm x 114 mm

THE SET INCLUDES:

- \cdot wire rope or synthetic rope
 - $\cdot \ \mathsf{rope} \ \mathsf{hook}$
 - control box
 - roller guides
 - or aluminum fairlead
 - · remote control
- and wireless remote control
 mounting screws

Rope winding speed and power consumption (the first rope layer on the drum)

rope load	kg		1814	3629	5443	
rope speed	m/min	5,9	4,4	2,8	0,9	
power consumption 12 V	amp	58	158	314	415	
power consumption 24 V	/ amp	35	89	178	225	

rope layer		1	2	3	4	5
rope pull	kg	5443	4299	3701	3211	2667
rope lenght on the drum	m	5,3	11,5	18,6	27,3	30,0



WATERPROOF ALUMINUM CONTROL BOX



DWM 12000 HDI

Dedicated for: off-road vehicles, tow trucks/ industrial vehicles

Voltage: 12 V **Motor:** 6,8 hp

Pulling rate: 12000 lb / 5443 kg

Gear: 3 stage planetary **Reduction:** 265:1 **Brake:** dynamic

Length of the wire rope: 30 mLength of the synthetic rope: 30 m

Overall size (LxWxH): 537 mm x 159 mm x 257 mm

Weight: 42 kg Screws: 4

Spacing of mounting screws: 254 mm x 114 mm

THE SET INCLUDES:

- wire rope or synthetic rope
 - · rope hook
 - control box
 - · roller guides
 - or aluminum fairlead
 - · remote control
- and wireless remote control
 - mounting screw

Rope winding speed and power consumption (the first rope layer on the drum)

rope load	kg		1814	3629	5443
rope speed	m/min	5,9	4,4	2,8	0,9
power consumpt	ion 12 V amp	58	158	314	415

Pulling force depending on rope layer

rope layer		1	2	3	4	5
rope pull	kg	5443	4299	3701	3211	2667
rope lenght on the drum	m	5,3	11,5	18,6	27,3	30,0



DWM 10000 HD

Dedicated for: off-road vehicles, tow trucks/industrial vehicles

Voltage: 12 V Motor: 6,8 hp

Pulling rate: 10000 lb / 4536 kg

Gear: 3 stage planetary **Reduction:** 265:1 **Brake:** dynamic

Length of the wire rope: 24 m **Length of the synthetic rope:** 25 m

Overall size (LxWxH): 450 mm x 159 mm x 243mm

Weight: 35 kg Screws: 4

Spacing of mounting screws: 164 mm x 114 mm

THE SET INCLUDES:

· wire rope or synthetic rope

- · rope hook
- · control box
- roller guides

or aluminum fairlead

· remote control

and wireless remote control

· mounting screw

Rope winding speed and power consumption (the first rope layer on the drum)

rope load	kg		1814	4536
rope speed	m/min	5,9	3,6	1,3
power consumption 12 V	amp	50	180	390

rope layer		1	2	3	4	5	
rope pull	kg	4536	3583	3084	2676	2270	
rope lenght on the drum	m	3,6	7,8	12,4	17,8	24,0	





DWM 3500 ST

Dedicated for: ATV / UTV, ploughs

Voltage: 12 V **Motor:** 1,2 hp

Pulling rate: 3500 lb / 1588 kg

Gear: single **Reduction:** 153:1 **Brake:** self-braking

Length of the wire rope: 15 m

Overall size (LxWxH): 320 mm x 100 mm x 100 mm

Weight: 10 kg Screws: 4

Spacing of mounting screws: $130 \text{ mm} \times 80 \text{ mm}$

THE SET INCLUDES:

- · wire rope
- · rope hook
- · control box
- · roller guides
- universal mounting plate
 switch on the steering wheel and wireless remote control
 - · mounting screws

Rope winding speed and power consumption (the first rope layer on the drum

rope load	kg		453	907	1588
rope speed	m/min	3,9	2,7	1,8	0,6
power consumption 12 V	amp	17	39	78	120

Pulling force depending on rope layer

rope layer		1	2	3	4	5	6
rope pull	kg	1588	1255	1079	937	778	619
rone lenght on the drum	m	16	3.5	5.7	84	11 3	15 O



DWM 2500 ST

Dedicated for: ATV / UTV, ploughs

Voltage: 12 V Motor: 0,9 hp

Pulling rate: 2500 lb / 1133 kg

Gear: single **Reduction:** 153:1 **Brake:** self-braking

Length of the wire rope: 10 m

Overall size (LxWxH): 280 mm x 100 mm x 101 mm

Weight: 9 kg Screws: 2

Spacing of mounting screws: 79 mm

THE SET INCLUDES:

- · wire rope
- · rope hook
- · control box
- · roller guides
- · universal mounting plate
- switch on the steering wheel and wireless remote control
 - mounting screws

Rope winding speed and power consumption (the first rope layer on the drum)

					L
rope load	kg		453	1133	
rope speed	m/min	3,5	2,4	0,8	
power consumption 12 V	amp	11	53	110	

rope layer		1	2	3	4	5
rope pull	kg	1133	895	770	668	555
rope lenght on the drum	m	1,5	3,4	5,5	8,2	10,0



DWM 2000 ST

Dedicated for: ATV / UTV, ploughs

Voltage: 12 V **Motor:** 0,9 hp

Pulling rate: 2000 lb / 907 kg

Gear: single **Reduction:** 153:1 **Brake:** self-braking

Length of the wire rope: 10 m

Overall size (LxWxH): 280 mm x 100 mm x 100 mm

Weight: 6 kg Screws: 2

Spacing of mounting screws: 79 mm



rope load	kg		453	907	
rope speed	m/min	3,5	2,4	1,0	
power consumption 12 V	amp	11	53	95	

Pulling force depending on rope layer

rope layer		1	2	3	4	5
rope pull	kg	907	716	617	535	444
rope lenght on the drum	m	1,8	3,8	6,2	8,9	10,0



THE SET INCLUDES:

- · wire rope
- · rope hook
- · control box
- switch on the steering wheelmounting screws





DRAGON WINCH HIGHLANDER

THE DRAGON WINCH HIGHLANDER SERIES HAS BEEN CREATED FOR OFF-ROAD VEHICLES. WITH A STRONGER MOTOR, HEAVY DUTY GEARBOX, DYNAMIC BRAKE AND REINFORCED CONSTRUCTION, IT IS THE BEST OPTION IN EXTREME OPERATING CONDITIONS.

DEDICATED FOR:



off-road vehicles



extreme ATV



UTV





DWH 15000 HD

Dedicated for: off-road vehicles

Voltage: 12 V Motor: 9 hp

Pulling rate: 15000 lb / 6803 kg

Gear: 3 stage planetary **Reduction:** 274:1 **Brake:** dynamic

Length of the wire rope: 28 m Length of the synthetic rope: 21 m

Overall size (LxWxH): 578 mm x 175 mm x 260 mm

Weight: 53 kg Screws: 4

Spacing of mounting screws: 254 mm x 114 mm

THE SET INCLUDES:

- \cdot wire rope
- · rope hook
- control box
- roller guides
 or aluminum fairlead
- · remote control
- and wireless remote control
 - · mounting screws

Rope winding speed and power consumption (the first rope layer on the drum)

rope load	kg		1814	3629	6803
rope speed	m/min	6,5	5,2	3,8	1,5
power consumption 12 V	amp	65	177	353	483

Pulling force depending on rope layer

rope layer		1	2	3	4	5
rope pull	kg	6803	5372	4626	4014	3333
rope lenght on the drum	m	5.2	11.0	18.3	26.6	28.0



DWH 12000 HD

Dedicated for: off-road vehicles

Voltage: 12 V Motor: 9 hp

Pulling rate: 12000 lb / 5443 kg

Gear: 3 stage planetary **Reduction:** 274:1 **Brake:** dynamic

Length of the wire rope: 28 m **Length of the synthetic rope:** 30 m

Overall size (LxWxH): 578 mm x 175 mm x 260 mm

Weight: 48 kg Screws: 4

Spacing of mounting screws: 254 mm x 114 mm

THE SET INCLUDES:

• wire rope or synthetic rope

- · rope hook
- · control box
- · roller guides
- or aluminum fairlead
 - · remote control
- and wireless remote control
 mounting screws

Rope winding speed and power consumption (the first rope layer on the drum

rope load	kg		1814	3629	5443	
rope speed	m/min	6,5	5,2	3,8	2,0	
power consumption 12 V	amp	65	177	353	470	

rope layer		1	2	3	4
rope pull	kg	5443	4299	3701	3211
rope lenght on the drum	m	5,8	12,7	20,0	28,0



DWH 9000 HD

Dedicated for: off-road vehicles

Voltage: 12 V **Motor:** 9 hp

Pulling rate: 9000 lb / 4082 kg

Gear: 3 stage planetary **Reduction:** 140:1 **Brake:** dynamic

Length of the wire rope: $28\ \text{m}$ Length of the synthetic rope: $30\ \text{m}$

Overall size (LxWxH): 578 mm x 175 mm x 260 mm

Weight: 46 kg Screws: 4

Spacing of mounting screws: 254 mm x 114 mm

Rope winding speed and power consumption (the first rope layer on the drum)

rope load	kg		1814	3629	4082
rope speed	m/min	10,9	8,8	6,2	5,4
power consumption 12 V	amp	70	211	422	480

Pulling force depending on rope layer

rope layer		1	2	3	4
rope pull	kg	4082	3225	2776	2408
rope lenght on the drum	m	6.2	13.8	22.0	28.0

superfast



THE SET INCLUDES:

wire rope or synthetic rope
rope hook
control box
roller guides
or aluminum fairlead

remote controland wireless remote controlmounting screws







DWH 4500 HDL

Dedicated for: ATV/UTV

Voltage: 12 V **Motor:** 1,9 hp

Pulling rate: 4500 lb / 2041 kg

Gear: 3 stage planetary

Reduction: 138:1 **Brake:** automatic

Length of the wire rope: 20 m

Overall size (LxWxH): 389 mm x 114 mm x 115 mm

Weight: 14 kg Screws: 4

Spacing of mounting screws: $168 \text{ mm} \times 76 \text{ mm}$

THE SET INCLUDES:

- · wire rope or synthetic rope
 - · rope hook
 - · control box
 - · roller guides
- switch on the steering wheel and wireless remote control
 - · mounting screws

Rope winding speed and power consumption (the first rope layer on the drum)

rope load	kg		453	907	2041
rope speed	m/min	6,3	5,3	4,5	2,1
power consumption 12 V	amp	23	40	81	160

Pulling force depending on rope layer

rope layer		1	2	3	4	5	
rope pull	kg	2041	1612	1388	1204	1001	
rope lenght on the drum	m	3.7	8.1	12.9	18.3	20.0	



DWH 4500 HD

Dedicated for: ATV/UTV

Voltage: 12 V Motor: 9 hp

Pulling rate: 4500 lb / 2041 kg

Gear: 3 stage planetary Reduction: 138:1 Brake: automatic

Length of the wire rope: 15 m **Length of the synthetic rope:** 15 m

Overall size (LxWxH): 337 mm x 114 mm x 115 mm

Weight: 13 kg Screws: 4

Spacing of mounting screws: 124 mm x 76 mm

THE SET INCLUDES:

- wire rope or synthetic rope
 rope hook
 - · control box
 - · roller guides
 - or aluminum fairlead
 - · remote control
- and wireless remote control
 mounting screws
 - · universal mounting
 - plate

Rope winding speed and power consumption (the first rope layer on the drum)

rope load	kg		453	907	2041
rope speed	m/min	6,3	5,3	4,5	2,1
power consumption 12 '	V amp	23	40	81	160

rope layer		1	2	3	4	5
rope pull	kg	2041	1612	1388	1204	1001
rope lenght on the drum	m	2.3	4.9	8.0	11.4	15.0





DWH 3500 HD

Dedicated for: ATV/UTV

Voltage: 12 V **Motor:** 1,6 hp

Pulling rate: 3500 lb / 1588 kg

Gear: 3 stage planetary

Reduction: 138:1 Brake: automato

Length of the wire rope: 15 m Length of the synthetic rope: 15 m $\,$

Overall size (LxWxH): 347 mm x 114 mm x 115 mm

Weigh: 12 kg Screws: 4

Spacing of mounting screws: 124 mm x 76 mm

THE SET INCLUDES:

- wire rope or synthetic rope
 - rope hook
 - · control box
 - · roller guides
- or aluminum fairlead
 <universal mounting plate
- · switch on the steering wheel
- and wireless remote control
 - · mounting screws

Rope winding speed and power consumption (the first rope layer on the drum)

rope load	kg		453	907	1587
rope speed	m/min	5,4	4,8	4,0	3,0
power consumption 12 V	amp	19	49	96	150

Pulling force depending on rope layer

rope layer		1	2	3	4	5
rope pull	kg	1587	1254	1079	967	778
rope lenght on the drum	m	2,5	5,3	8,4	12,2	15,0



DWH 3000 HD

Dedicated for: ATV/UTV

Voltage: 12 V Motor: 1,4 hp

Pulling rate: 3000 lb / 1360 kg

Gear: 3 stage planetary **Reduction:** 138:1 **Brake:** automatic

Length of the wire rope: 15~mLength of the synthetic rope: 15~m

Overall size (LxWxH): 347 mm x 114 mm x 115 mm

Weight: 12 kg Screws: 4

Spacing of mounting screws: 124 mm x 76 mm

THE SET INCLUDES:

- wire rope or synthetic rope
 rope hook
 control box
 roller guides
 - or aluminum fairlead
- universal mounting plate
 switch on the steering wheel and wireless remote control
 mounting screws

Rope winding speed and power consumption (the first rope layer on the drum)

rope load	kg		453	907	1360
rope speed	m/min	4,9	4,3	3,5	2,8
power consumption 12 V	amp	18,7	50	101	135

rope layer		1	2	3	4	5
rope pull	kg	1360	1074	925	802	666
rope lenght on the drum	m	2,6	5,4	8,6	12,4	15,0



special vehicles



industrial vehicles

DRAGON WINCH HIDRA







DWHI 20000 HD

Dedicated for: special trucks, tow trucks /

industrial vehicles Power: hydraulic

Pulling rate: 20000 lb / 9072 kg

Pulling force depending on rope layer:

- first layer of rope: 9072 kg - last layer of rope: 6187 kg

Rope winding speed:

- first layer of rope: 4,2 m/min - last layer of rope: 5,6 m / min Max oil pressure: 17,5 Mpa Max oil flow: 60 I / min

Overall size (LxWxH): 590 mm x 269 mm x 217 mm Drum capacity: 31 m (max recommended length

of rope on the drum) Number of rope layers: 4

Weight: 72 kg

THE SET INCLUDES:

wire rope (to be wound on the drum by the customer) · rope hook · roller guides mounting screws

DWHI 16000 HD

Dedicated for: special trucks, tow trucks /

industrial vehicles Power: hydraulic

Pulling rate: 16000 lb / 7257 kg

Pulling force depending on rope layer:

- first layer of rope: 7257 kg - last layer of rope: 4944 kg

Rope winding speed:

- first layer of rope: 4,2 m / min - last layer of rope: 5,6 m/min Max oil pressure: 17,5 Mpa Max oil flow: 60 I / min

Overall size (LxWxH): 590 mm x 269 mm x 217 mm **Drum capacity:** 31 m (max recommended length

of rope on the drum) Number of rope layers: 4

Weight: 72 kg

THE SET INCLUDES:

wire rope (to be wound on the drum by the customer) · rope hook · roller guides mounting screws

DRAGON WINCH HIDRA





DWHI 12000 HD

Dedicated for: special trucks, tow trucks /

industrial vehicles **Power:** hydraulic

Pulling rate: 12000 lb / 5443 kg

Pulling force depending on rope layer:

first layer of rope: 5443 kg
last layer of rope: 2851kg
Rope winding speed:

first layer of rope: 4,2 m / minlast layer of rope: 6,8 m / min

Max oil pressure: 16 Mpa Max oil flow: 40 I / min

Overall size (LxWxH): 590 mm x 269 mm x 217 mm


Drum capacity: max 45 m **Number of rope layers:** max 5

Weight: 55 kg





DRAGON WINCH series HIDRA



Pulling rate: 66 000 lb / 30 000 k Speed of the rope: 5,5 m/min Pressure of oil: 17 / 170 MPa/Bar

Oil flow: 120 I/min


Overall size (LxWxH): 1 337 mm x 618 mm x 530 mm Size of the drum (LxWxH): 530 mm x 280 mm x 360 mm Capacity of the drum: 54 m (max recommended length

DWHI 660 HD

of the rope on the drum)

Diameter of the wire rope (recommended): 32 mm

Weight: 570 kg



DWHI 450 HD

Dedicated for: special trucks, tow trucks / industrial vehicles

Power supply: hydraulic

Pulling rate: 45 000 lb / 20 000 kg **Speed of the rope:** 6 m/min **Pressure of oil:** 17/170 MPa/Bar


Oil flow: 120 I/min

Overall size (LxWxH): 1 250 mm x 400 mm x 390 mm Size of the drum (LxWxH): 400 mm x 210 mm x 340 mm Capacity of the drum: 45 m (max recommended lenght

of the rope on the drum)

Diameter of the wire rope (recommended): 26 mm

Weight: 295 kg





DWHI 300 HD

Dedicated for: special trucks, tow trucks / industrial vehicles **Power supply:** hydraulic

Pulling rate: 30 000 lb / 13 605 kg Speed of the rope: 7 m /min Pressure of oil: 17/170 MPa/Bar

Oil flow: 60 I/min

Overall size (LxWxH): $1120 \text{ mm} \times 470 \text{ mm} \times 410 \text{ mm}$ Size of the drum (LxWxH): $390 \text{ mm} \times 190 \text{ mm} \times 340 \text{ mm}$ Capacity of the drum: 59 m (max recommended lenght

of the rope on the drum)

Diameter of the wire rope (recommended): 18 mm

Weight: 265 kg



DRAGON WINCH series HIDRA



DWHI 18000 HD

Dedicated for: special trucks, tow trucks / industrial vehicles

Voltage: hydraulic

Pulling rate: 18000 lb / 8165 kg

Gear: 2 stage planetary

Reduction: 33:1

Max. pressure of oil: 14 Mpa Max. oil flow: 5-65 I / min

Brake: dynamic

Length of the wire rope: 28 m

Overall size (LxWxH): 545 mm x 206 mm x 257 mm

Weight: 68 kg

Spacing of mounting screws: 254 mm x 114 mm

THE SET INCLUDES: · wire rope · rope hook · roller guides · mounting screws

Rope winding speed and power consumption (the first rope layer on the drum)

rope load	kg		2267	4535	8165	
rope speed	m/min	0,5	1,2	3	5,5	
pressure	Мра	2	4,3	8,7	14	
oil flow	l/min	5	10	20	65	

Pulling force depending on rope layer

rope layer		1	2	3	4	
rope pull	kg	8165	6597	5534	4767	
rope lenght on the drum	m	5	11,5	19	28	



DWHI 15000 HD

Dedicated for: special trucks, tow trucks / industrial vehicles

Voltage: hydraulic

Pulling rate: 15000 lb / 6803 kg

Gear: 2 stage planetary

Reduction: 25:1

Max. pressure of oil: 14,5 Mpa Max. oil flow: 5-45 I / min

Brake: dynamic

Length of the wire rope: 28 m

Overall size (LxWxH): 520 mm x 186 mm x 240 mm

Weight: 66 kg

Spacing of mounting screws: 254 mm x 114 mm



Rope winding speed and power consumption (the first rope layer on the drum)

rope load	kg		2267	4535	6803
rope speed	m/min	0,7	2,5	4,6	5,1
pressure	Мра	2	6,6	11,5	14,5
oil flow	l/min	5	19,2	20	45

rope layer		1	2	3	4
rope pull	kg	6803	5498	4612	3972
rope lenght on the drum	m	4,8	12	21	28



DRAGON WINCH EN

Winches compliant with EN 14492-2 Standard intended for:





special vehicles

tow trucks, industrual vehicles

DRAGON WINCH seria EN







DWT 18000 HDL EN

Dedicated for: special trucks, tow trucks / industrial vehicles

Voltage: 24 V Motor: 9,5 hp

Pulling rate: 18000 lb / 8165 kg

Reduction: 463:1
Gear: 3 stage planetary
Brake: dynamic

Length of the wire rope: 30 m (max 36)

Overall size (LxWxH): 745 mm x 217 mm x 271 mm

Weight: 91 kg Screws: 8

Spacing of mounting screws: 365 mm x 114 mm

/ 365 mm x 164 mm

THE SET INCLUDES:

- · wire rope
- · rope hook
- · control box
- · roller guides
- remote control
- and wireless remote control
 mounting screws
 - safety switch 200A
- Rope winding speed and power consumption (the first rope layer on the drum)

rope load	kg	0	2721	5443	8165
rope speed	m/min	5,0	4,0	3,3	1,9
power consumption 24 V	amp	50	124	248	320

Pulling force depending on rope layer

rope layer		1	2	3
rope pull	kg	8165	6450	5552
rope lenght on the drum	m	11	23,5	30

DWHI 180 HD EN

Dedicated for: special trucks, tow trucks /

industrial vehicles **Power:** hydraulic

Pulling rate: 18000 lb / 8165 kg

Pulling force depending on rope layer:

first layer of rope: 8165 kg
 last layer of rope: 5552 kg
 Rope winding speed:

first layer of rope: 4,4 m / min
last layer of rope: 6,1 m / min
Max oil pressure: 17,5 Mpa
Max oil flow:60 I / min

Overall size (LxWxH): 700 mm x 271 mm x 220 mm

Drum capacity: 31 m **Number of rope layers:** 3

Weight: 91 kg







DWM 13500 HD EN

Dedicated for: special trucks

Voltage: 12 V or 24 V Motor: 7.8 hp

Pulling rate: 13500 lb / 6123 kg

Gear: 3 stage planetary
Reduction: 358:1
Brake: dynamic

Length of the wire rope: 31 m

Overall size (LxWxH): 574 mm x 196 mm x 266 mm

Weight: 57 kg Screws: 4

Spacing of mounting screws: $254 \text{ mm} \times 114 \text{ mm}$

THE SET INCLUDES:

- · wire rope
- · rope hook
- control box
- $\cdot \ \text{roller guides} \\$
- remote control and wireless remote control
 - · mounting screws
 - safety switch 200A

Rope winding speed and power consumption (the first rope layer on the drum)

rope load	kg		1814	3629	6123
rope speed	m/min	5,7	4,4	2,0	0,8
power consumption 12 V	amp	68	157	280	420
power consumption 24 V	amp	40	89	157	235

Pulling force depending on rope layer

rope layer		1	2	3	4	
rope pull	kg	6123	4837	4163	3613	
rope lenght on the drum	m	4,8	12,0	21,0	31,0	



DWM 12000 HD EN

Dedicated for: special trucks

Voltage: 12 V or 24 V

Motor: 7,8 hp

Pulling rate: 12000 lb / 5443 kg

Gear: 3 stage planetary **Reduction:** 358:1 **Brake:** dynamic

Length of the wire rope: 31 m

Overall size (LxWxH): 574 mm x 196 mm x 266 mm

Weight: 55 kg Screws: 4

Spacing of mounting screws: 254 mm x 114 mm


THE SET INCLUDES:

- wire rope
- · rope hook
- control box
- roller guidesremote control
- and wireless remote control
 - mounting screws safety switch 200A

Rope winding speed and power consumption (the first rope layer on the drum)

rope load	kg		1814	3629	5443
rope speed	m/min	5,7	4,4	2,0	1,0
power consumption 12 V	amp	68	157	280	370
power consumption 24 V	amp	40	89	157	205

rope layer		1	2	3	4
rope pull	kg	5443	4299	3701	3211
rope lenght on the drum	m	4,8	12,0	21,0	31,0





DRAGON WINCH PORTABLE WINCHES



DWP 5000

Dedicated for: boats

Voltage: 12 V **Motor:** 2,9 hp

Pulling rate: 5 000 lb/ 2 265 kg

Reduction: 717:1

Brake: self-braking

Length of the wire rope: 9 m Winding/unwinding rope: electric Overall size: 255 mm x 268 mm x 219mm

Weight: 17kg

THE SET INCLUDES:

- wire rope with hook
 - mounting plate
 - power cable
 - hand crank
 - remote control

DWP 3500

Dedicated for: boats

Voltage: 12 V Motor: 1,3 hp

Pulling rate: 3 500 lb / 1 588 kg

Reduction: 717:1 **Brake:** self-braking

Length of the wire rope: 10 m **Winding/unwinding rope:** electric **Overall size:** 241 mm x 247 mm x 212 mm

Weight: 15 kg

THE SET INCLUDES:

- wire rope with hook
 - mounting plate
 - power cablehand crank
 - · remote control





DRAGON WINCH INDUSTRIAL

THE DRAGON WINCH INDUSTRIAL SERIES - VERY DURABLE AND SOLID WINCHES WITH A 230 V POWER SUPPLY.

THE OFFER COMPRISES ALSO: ELECTRICAL TROLLEYS MANUAL TROLLEYS GUIDE RAILS.

DRAGON WINCH series INDUSTRIAL





DWI 500/990 230V

Dedicated for: workshops

Voltage: 230 V

Pulling rate with a single rope: 500 kg **Pulling rate with a double rope:** 990 kg

Pulling height: 12 m / 6 m **Brake:** automatic

Turn - off switches: limit switches

and emergency switches

Remote control: controlling up and down

Weight: 31 kg



DWI 300/600 230 V

Dedicated for: workshops

Voltage: 230 V

Pulling rate with a single rope: 300 kg Pulling rate with a double rope: 600 kg

Pulling height: 12 m / 6 m

Brake: automatic

Turn - off switches: limit switches

and emergency switches

Remote control: controlling up and down

Weight: 17,5 kg

SET OF HOIST WITH ELECTRIC TROLLEY





DWI 400/800 230 V

Dedicated for: workshops

Voltage: 230 V

Pulling rate with a single rope: 400 kg Pulling rate with a double rope: 800 kg

Pulling height: 12 m / 6 m

Brake: automatic

Turn - off switches: limit switches

and emergency switches

Remote control: controlling up and down

Weight: 19 5 kg



DWI 125/250 230 V

Dedicated for: workshops

Voltage: 230 V

Pulling rate with a single rope: 125 kg Pulling rate with a double rope: 250 kg

Pulling height: 12 m / 6 m

Brake: automatic

Turn - off switches: limit switches

and emergency switches

Remote control: controlling up and down

Weight: 11 kg



DRAGON WINCH series INDUSTRIAL





DWI 1 T ELECTRICAL TROLLEY 1 T

Dedicated for: workshops **Nominal lifting:** 1 T

Standard operating height: 3 m

Weight: 19 kg

DWI 0,5 T ELECTRICAL TROLLEY 0,5 T

Dedicated for: workshops **Nominal lifting:** 0,5 T

Standard operating height: 3 m

Weight: 19 kg



DWI 0,5 T MANUAL TROLLEY 0,5 T

Dedicated for: workshops **Nominal lifting:** 0,5 T

Standard operating height: 3 m

Weight: 11 kg

DWI 1T MANUAL TROLLEY 1T

Dedicated for: workshops **Nominal lifting:** 1 T

Standard operating height: 3 m

Weight: 13 kg



DRAGON WINCH HAND CRANK

WINCHES WITH A STRONG STEEL CONSTRUCTION.
INTENDED FOR PULLING:







DRAGON WINCH series HAND CRANK





DWK 35 VC

Dedicated for: workshops, tow trucks / industrial vehicles, boats

Max. pulling rate: 3 500 lb/ 1 588 kg

Lenght of the rope: 10 m **Diemeter of the rope:** 6 mm

Weight: 7



DWK 25 C

Dedicated for: workshops,

tow trucks / industrial vehicles, boats **Max. puilling rate:** 2 500 lb / 1133 kg

Lenght of the rope: 10 m **Diemeter of the rope:** 6 mm

Weight: 6 kg

Winches with friction brake



DWKO 2600 HD

Dedicated for: workshops, tow trucks/ industrial vehicles, boats **Max. pulling rate:** 2 600 lb/ 1 200 kg

Lenght of the rope: 17 m **Diemeter of the rope:** 6 mm

Weight: 12 kg



DWKO 1200 HD

Dedicated for: workshops, tow trucks / industrial vehicles, boats **Max. pulling rate:** 1200 lb / 540 kg

Lenght of the rope: 10 m **Diemeter of the rope:** 5 mm

Weight: 4,5 kg



DWKO 1800 HD

Dedicated for: workshops, tow trucks / industrial vehicles, boats **Max. pulling rate:** 1800 lb / 810 kg

Lenght of the rope: 10 m **Diemeter of the rope:** 5 mm

Weight: 9 kg



DWKO 800 HD

Dedicated for: workshops,

tow trucks / industrial vehicles, boats **Max. pulling rate:** 800 lb / 360 kg

Lenght of the rope: 10 m

Diemeter of the rope: 5 mm

Weight: 3,4 kg



DRAGON WINCH series HAND CRANK



DWK 35 V

2-speed winch

Dedicated for: workshops, tow trucks / industrial vehicles, boats Max. pulling rate: 3 500 lb/ 1 588 kg **Lenght of the rope:** 10 m Diemeter of the rope: 6 mm

Weight: 5,7 kg

DWK 25 V

2-speed winch

Dedicated for: workshops, tow trucks / industrial vehicles, boats Max. puilling rate: 2 500 lb / 1 133 kg Lenght of the rope/belt: 10 m Diemeter of the rope: 6 mm

Weight: 5 kg





DWK 25

Dedicated for: workshops, tow trucks / industrial vehicles, boats Max. pulling rate: 2 500 lb/1133 kg Lenght of the rope/belt: 10 m Diemeter of the rope: 6 mm

Weight: 5 kg

DWK 16

Dedicated for: workshops, tow trucks / industrial vehicles, boats Max. pulling rate: 1600 lb/725 kg Lenght of the rope/belt: 10 m Diemeter of the rope: 5 mm

Weight: 3,4 kg

DWK 12

Dedicated for: workshops, tow trucks / industrial vehicles, boats Max. pulling rate: 1200 lb/540 kg Lenght of the rope/belt: 10 m Diemeter of the rope: 4 mm

Weight: 3,2 kg



THE OFFER COMPRISES SPARE PARTS AND ACCESSOIRES FOR ALL DRAGON WINCH MODELS.

SELECTED ACCESSOIRES ARE SHOWN IN THE CATALOGUE.



ROPE HOOK

Available:

- · 16000-22000 lbs
- · 8000-14000 lbs
- ATV



TREE BELT

Available:

- 20 m 5 T
- •9 m 8 T
- •3 m 9 T
- 1,5 m 9 T
- 1,5 m 4 T



SNATCH BLOCK

Available:

- 15 T
- 10 T
- ·8T
- 4 T



SNATCH BLOCK WITH ATV HOOK

Available:

• 2 T



WIRE ROPE

Available:

- 16000-22000 lbs
- 9000-14000 lbs
- 8000 lbs
- ATV 20 m
- ATV 15 m



SHACKLE

Available:

- · shackle 1/1 8,5 T
- · shackle 7/8 6.5 T
- · shackle 3/4 4,75 T
- · shackle 5/8 3,25 T



SYNTETIC ROPE

Available:

- · 4x4 9000-13000 lbs
- •11 mm 16000 lbs
- · 12 mm 18000-22000 lbs
- · 4x4 9000-13000 lbs (in protective sleeve)
- TRUCK 16000-18000 lbs (in protective sleeve) • ATV

KINETIC ROPE

Available:

- 28mm 12m 22 T
- 28mm 10m 15,5 T
- · 28mm 8m 15,5 T
- · 28mm 6m 15,5 T



THE OFFER COMPRISES ALSO SPECIAL ROPES

- LENGHT, PULLING RATE AND DIAMETER IN ACCORDANCE WITH CUSTOMER NEEDS.



MOUNTING PLATE 4X4

MOUNTING PLATE 4X4 PORTABLE

· 10000-13000 lbs (series DWM)

 Portable · Mounted in the place of the hook





MOUNTING PLATE

UNIVERSAL

- · DWM 12000-13000
- DWT 14000-18000, DWH 9000-15000

MOUNTING PLATE

UNIVERSAL

· ATV



ROPE TENSIONER



ROLLER GUIDES

Available:

- · DWM 12000-13000
- DWM 8000
- DWM 2500-3500 ST
- DWH 9000-15000
- DWH 4500 HDL
- · DWH 3000-4500
- DWT 14000-22000 • DWHI 12000-18000
- •12000-20000 lbs SUPER STRONG



FAIRLEAD

- DWM. DWH. DWT 9000-18000
- · ATV
- 9000-22000 SUPER STRONG
- · 9000-18000 LOGO





BAG FOR ACCESSORIES

OFF-ROAD

DRAGON

WINCH COVER

Available:

- TRUCK
- 4X4
- ATV
- Farm Jack
- · Hand crank winches



TRAPS

Traps are made of strengthened plastic. Ideal for use in swampy areas. Sold in double pack.



BAG 4X4


- Tree belt 3 m
- · 2 x shackle 7/8
- · Snatch block 8T
- Gloves



FARM JACK

Available:

- · Farm Jack 48
- · Farm Jack 60



HIGH-CURRENT CONNECTORS

8000-22000 lbs ATV



SAFETY SWITCH

200A 300 A 450 A





DRAGON WINCH COMPRESSORS







Compressor - big TRUCK

Voltage: 12 V

Max. amperage: 45 amp Max. pressure: 150 PSI Performance: 100 I/min

Continuous operation time: max 15 min

Weight: 7,35 kg

Voltage: 12 V

Weight: 3 kg

Max. amperage: 23 amp

Max. pressure: 150 PSI

Performance: 60 l/min



DWK-S LED

Compressor - small with LED flashlight.

Continuous operation time: max 15 min





DWK-S

Compressor - medium

Voltage: 12 V

Max. amperage: 23 amp Max. pressure: 150 PSI Performance: 60 l/min

Continuous operation time: max 15 min

DWK-DHD

Compressor - big

Voltage: 12 V

Max. amperage: 45 amp Max. pressure: 150 PSI Performance: 150 I/min

Continuous operation time: max 15 min

Weight: 7,35 kg



DWK-M

Compressor - small

Voltage: 12 V

Max. amperage: 12 amp Max. pressure: 140 PSI Performance: 27 l/min

Continuous operation time: max 15 min

Weight: 1,5 kg

WE OFFER SPARE PARTS FOR ALL WINCHES













